

# ROLLER FAIRLEADS

Possible configurations are:

TYPE	Positie van de rollen		TYPE	Positie van de rollen	
	Bovenaanzicht	Zij aanzicht		Bovenaanzicht	Zij aanzicht
PW ...F BW ...F			PW ...FL BW ...FL		
PW .../1 LF BW .../1 LF			PW .../1 LFL BW .../1 LFL		
PW .../1 RF BW .../1 RF			PW .../1 RFL BW .../1 RFL		
PW .../2 F BW .../2 F			PW .../2 FL BW .../2 FL		
PDW...F BDW...F			PDW...FL BDW...FL		
PDW.../1 LF BDW.../1 LF			PDW.../1 LFL BDW.../1 LFL		
PDW.../1 MF BDW.../1 MF			PDW.../1 MFL BDW.../1 MFL		
PDW.../1 RF BDW.../1 RF			PDW.../1 RFL BDW.../1 RFL		
PDW.../2 F BDW.../2 F			PDW.../2 FL BDW.../2 FL		
PDW.../2 LF BDW.../2 LF			PDW.../2 LFL BDW.../2 LFL		
PDW.../2 RF BDW.../2 RF			PDW.../2 RFL BDW.../2 RFL		
PDW.../3 F BDW.../3 F			PDW.../3 FL BDW.../3 FL		

PW ... : roller fairlead for 1 cable  
 PDW ... : double roller fairlead for 2 cables  
 BW ... : roller fairlead for 1 cable  
 BDW ... : double roller fairlead for 2 cables  
 ... K : maintenance-poor artificial bronze / Niro bearing  
 ... Au : wire stroke between the vertical rollers on the underside  
 ... Ao : wire stroke between the vertical rollers on the upper side

mounting into the bulwark  
 mounting into the bulwark  
 mounting free on deck  
 mounting free on deck



Lemans Nederland B.V.  
 Canadaweg 8  
 4661 PZ Halsteren  
 The Netherlands

Tel.: +31(0) 164 680097  
 Fax: +31(0) 164 681971  
 E-mail: [info@lemans-nederland.eu](mailto:info@lemans-nederland.eu)  
 Website: [www.lemans-nederland.nl](http://www.lemans-nederland.nl)